



FAG

16076-M

Deep groove ball bearing

Deep groove ball bearing 160...-M, single row, solid brass cage

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	Without	Not sealed
Cage	M	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	380 mm	Bore diameter
D	560 mm	Outside diameter
B	57 mm	Width
C _r	375.000 N	Basic dynamic load rating, radial
C _{0r}	620.000 N	Basic static load rating, radial
C _{ur}	16.600 N	Fatigue load limit, radial
n _G	1.960 1/min	Limiting speed
n _{gr}	1.290 1/min	Reference speed
≈m	51,7 kg	Masa



Mounting dimensions

$d_{a\min}$	394,6 mm	Minimum diameter shaft shoulder
$D_{a\max}$	545,4 mm	Maximum diameter of housing shoulder
$r_{a\max}$	3 mm	Maximum fillet radius

Dimensions

$r_{\min}$	4 mm	Minimum chamfer dimension
D_1	498,25 mm	Shoulder diameter outer ring
d_1	443,25 mm	Shoulder diameter inner ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

Calculation factors

f_0	16,5	Calculation factor
-------	------	--------------------

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe