



FAG

16101-A

Deep groove ball bearing

Deep groove ball bearing 161, single row,
steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Changed internal design	A	Design variant A
Sealing	Without	Not sealed
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	12 mm	Bore diameter
D	30 mm	Outside diameter
B	8 mm	Width
C _r	5.400 N	Basic dynamic load rating, radial
C _{0r}	2.370 N	Basic static load rating, radial
C _{ur}	161 N	Fatigue load limit, radial
n _G	38.500 1/min	Limiting speed
n _{gr}	25.000 1/min	Reference speed
m	25 g	Masa



Mounting dimensions

$d_{a \min}$	14,4 mm	Minimum diameter shaft shoulder
$D_{a \max}$	27,6 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0,3 mm	Maximum fillet radius

Dimensions

$r_{\min}$	0,3 mm	Minimum chamfer dimension
D_1	23,43 mm	Shoulder diameter outer ring
D_2	25,7 mm	Caliber diameter outer ring
d_1	17,2 mm	Shoulder diameter inner ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Calculation factors

f_0	13,1	Calculation factor
-------	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia