


**203-XL-KRR-AH02** [🔗](#)

Deep groove ball bearing

Radial insert ball bearings 2..-KRR, cylindrical outer ring, inner ring for fit, R seals on both sides

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Sealing

KRR

Lip seals on both sides

Main Dimensions & Performance Data

d	16,2 mm	Bore diameter
D	40 mm	Outside diameter
B	18,3 mm	Width
C _r	9.800 N	Basic dynamic load rating, radial
C _{0r}	4.750 N	Basic static load rating, radial
m	0,08 kg	Masa

Dimensions

D ₁	32,6 mm	Outside diameter seal
C	12 mm	Width, outer ring
C ₂	12 mm	Sealing total width
d ₁	24,2 mm	Rib diameter inner ring
r _{min}	0,6 mm	Minimum chamfer dimension

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.



Calculation factors

f ₀	13	Calculation factor
----------------	----	--------------------

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne