



206-XL-NPP-B

Self-aligning deep groove ball bearings

Self-aligning deep groove ball bearings 2...-NPP-B, spherical outer ring, inner ring for fit, R seals on both sides

X-life

Informacje techniczne

Twoja aktualna wersja produktu

|                        |     |           |
|------------------------|-----|-----------|
| Sealing                | NPP |           |
| Shape of outer surface | B   | Spherical |

Main Dimensions & Performance Data

|      |          |                                   |
|------|----------|-----------------------------------|
| d    | 30 mm    | Bore diameter                     |
| D SP | 62 mm    | Outside diameter                  |
| B    | 16 mm    | Width                             |
| C r  | 20.700 N | Basic dynamic load rating, radial |
| C 0r | 11.300 N | Basic static load rating, radial  |
| ≈m   | 0,19 kg  | Masa                              |

Dimensions

|       |         |                                 |
|-------|---------|---------------------------------|
| d 2   | 37,3 mm | Rib diameter sealing inner ring |
| r min | 1 mm    | Minimum chamfer dimension       |

Temperature range

|       |        |                            |
|-------|--------|----------------------------|
| T min | -20 °C | Operating temperature min. |
| T max | 100 °C | Operating temperature max. |

Calculation factors

|     |      |                    |
|-----|------|--------------------|
| f 0 | 13,8 | Calculation factor |
|-----|------|--------------------|



### Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne
-  Nieosiowość statyczna