



FAG


22232-E1A-XL-K-2RSR-M

Spherical Roller Bearing

Spherical Roller Bearing 222...-E1A-XL-K-2RSR-M, symmetrical 2 outer ribs, sealed

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E1A	Without central rip
Bore type	K	Tapered, taper 1:12
Cage	M	Brass Cage
Relubrication	Standard	
Special material	Standard	

Main Dimensions & Performance Data

d	160 mm	Bore diameter
D	290 mm	Outside diameter
B	80 mm	Width
C _r	1.080.000 N	Basic dynamic load rating, radial
C _{0r}	1.300.000 N	Basic static load rating, radial
C _{ur}	128.000 N	Fatigue load limit, radial
n _G	700 1/min	Limiting speed
m	22 kg	Masa



Mounting dimensions

d _{a min}	174 mm	Minimum diameter shaft shoulder
D _{a max}	276 mm	Maximum diameter of housing shoulder
r _{a max}	2,5 mm	Maximum recess radius
d _{a max}	190 mm	Maximum diameter of shaft shoulder
d _{b min}	170 mm	Minimum cavity diameter of the sleeve
B _{a min}	14 mm	Minimum cavity width of the sleeve

Dimensions

r _{min}	3 mm	Minimum chamfer dimension
D ₁	258,3 mm	Bore diameter outer ring
d _s	8 mm	Diameter lubrication hole
n _s	15 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.

Calculation factors

e	0,24	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	2,79	Dynamic axial load factor
Y ₂	4,15	Dynamic axial load factor
Y ₀	2,73	Static axial load factor

Additional information

H3132	Adapter sleeve
AH3132A	Withdrawal sleeve



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna