



FAG

22234-E1A-XL-K-M-C4

Spherical Roller Bearing

Spherical roller bearing 222...-E1A-XL-K-M,  
symmetric 2 outer ribs

X-life

Informacje techniczne



Twoja aktualna wersja produktu

|                           |              |                                   |
|---------------------------|--------------|-----------------------------------|
| Design                    | E1A          | Without central rip               |
| Bore type                 | K            | Tapered, taper 1:12               |
| Cage                      | M            | Brass Cage                        |
| Radial internal clearance | C4 (Group 4) | Internal clearance larger than C3 |
| Relubrication             | Standard     |                                   |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 170 mm      | Bore diameter                     |
| D               | 310 mm      | Outside diameter                  |
| B               | 86 mm       | Width                             |
| C <sub>r</sub>  | 1.320.000 N | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 1.570.000 N | Basic static load rating, radial  |
| C <sub>ur</sub> | 144.000 N   | Fatigue load limit, radial        |
| n <sub>G</sub>  | 2.550 1/min | Limiting speed                    |
| n <sub>gr</sub> | 1.780 1/min | Reference speed                   |
| ≈m              | 27 kg       | Masa                              |



Mounting dimensions

|                    |        |                                       |
|--------------------|--------|---------------------------------------|
| d <sub>a min</sub> | 187 mm | Minimum diameter shaft shoulder       |
| D <sub>a max</sub> | 293 mm | Maximum diameter of housing shoulder  |
| r <sub>a max</sub> | 3 mm   | Maximum recess radius                 |
| d <sub>a max</sub> | 199 mm | Maximum diameter of shaft shoulder    |
| d <sub>b min</sub> | 180 mm | Minimum cavity diameter of the sleeve |
| B <sub>a min</sub> | 10 mm  | Minimum cavity width of the sleeve    |

Dimensions

|                  |          |                                    |
|------------------|----------|------------------------------------|
| r <sub>min</sub> | 4 mm     | Minimum chamfer dimension          |
| D <sub>1</sub>   | 275,4 mm | Bore diameter outer ring           |
| d <sub>2</sub>   | 199,8 mm | Raceway diameter of the inner ring |
| d <sub>s</sub>   | 9,5 mm   | Diameter lubrication hole          |
| n <sub>s</sub>   | 17,7 mm  | Width of lubricating groove        |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -30 °C | Operating temperature min. |
| T <sub>max</sub> | 200 °C | Operating temperature max. |

Calculation factors

|                |      |                                                                                  |
|----------------|------|----------------------------------------------------------------------------------|
| e              | 0,26 | Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y |
| Y <sub>1</sub> | 2,6  | Dynamic axial load factor                                                        |
| Y <sub>2</sub> | 3,87 | Dynamic axial load factor                                                        |
| Y <sub>0</sub> | 2,54 | Static axial load factor                                                         |

Additional information

|         |                   |
|---------|-------------------|
| H3134   | Adapter sleeve    |
| AH3134A | Withdrawal sleeve |



### Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Nieosiowość dynamiczna