



FAG

22236-E1-XL-K-C4

Spherical Roller Bearing

Spherical roller bearings 222...-E1-K, main dimensions to DIN 635-2, with tapered bore, taper 1:12

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E1	Without central rip
Bore type	K	Tapered, taper 1:12
Cage	JPA	Sheet metal cage
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Relubrication	Standard	

Main Dimensions & Performance Data

d	180 mm	Bore diameter
D	320 mm	Outside diameter
B	86 mm	Width
C _r	1.360.000 N	Basic dynamic load rating, radial
C _{0r}	1.680.000 N	Basic static load rating, radial
C _{ur}	153.000 N	Fatigue load limit, radial
n _G	2.470 1/min	Limiting speed
n _{gr}	1.670 1/min	Reference speed
≈m	28,005 kg	Masa



Mounting dimensions

d _{a min}	197 mm	Minimum diameter shaft shoulder
d _{a max}	211 mm	Maximum diameter of shaft shoulder
D _{a max}	303 mm	Maximum diameter of housing shoulder
r _{a max}	3 mm	Maximum recess radius
d _{b min}	191 mm	Minimum cavity diameter of the sleeve
B _{a min}	18 mm	Minimum cavity width of the sleeve

Dimensions

r _{min}	4 mm	Minimum chamfer dimension
D ₁	285,9 mm	Bore diameter outer ring
d ₂	211,3 mm	Raceway diameter of the inner ring
d _s	9,5 mm	Diameter lubrication hole
n _s	17,7 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,25	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	2,71	Dynamic axial load factor
Y ₂	4,04	Dynamic axial load factor
Y ₀	2,65	Static axial load factor

Additional information

H3136	Adapter sleeve
AH2236G	Withdrawal sleeve



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna