



**FAG****22313-E1A-XL-M-C3**

Spherical Roller Bearing

Spherical roller bearing 223...-E1A-XL-M,  
symmetric 2 outer ribs**X-life**

## Informacje techniczne



## Twoja aktualna wersja produktu

|                           |              |                                   |
|---------------------------|--------------|-----------------------------------|
| Design                    | E1A          | Without central rip               |
| Bore type                 | Z            | Cylindrical                       |
| Cage                      | M            | Brass Cage                        |
| Radial internal clearance | C3 (Group 3) | Internal clearance larger than CN |
| Relubrication             | Standard     |                                   |

## Main Dimensions &amp; Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 65 mm       | Bore diameter                     |
| D               | 140 mm      | Outside diameter                  |
| B               | 48 mm       | Width                             |
| C <sub>r</sub>  | 350.000 N   | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 365.000 N   | Basic static load rating, radial  |
| C <sub>ur</sub> | 33.500 N    | Fatigue load limit, radial        |
| n <sub>G</sub>  | 5.000 1/min | Limiting speed                    |
| n <sub>gr</sub> | 3.800 1/min | Reference speed                   |
| ≈m              | 3,545 kg    | Masa                              |

## Mounting dimensions

|                    |        |                                      |
|--------------------|--------|--------------------------------------|
| d <sub>a min</sub> | 77 mm  | Minimum diameter shaft shoulder      |
| D <sub>a max</sub> | 128 mm | Maximum diameter of housing shoulder |
| r <sub>a max</sub> | 2,1 mm | Maximum recess radius                |



Dimensions

|                  |          |                                    |
|------------------|----------|------------------------------------|
| r <sub>min</sub> | 2,1 mm   | Minimum chamfer dimension          |
| D <sub>1</sub>   | 119,3 mm | Bore diameter outer ring           |
| d <sub>2</sub>   | 83,2 mm  | Raceway diameter of the inner ring |
| d <sub>s</sub>   | 4,8 mm   | Diameter lubrication hole          |
| n <sub>s</sub>   | 9,5 mm   | Width of lubricating groove        |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -30 °C | Operating temperature min. |
| T <sub>max</sub> | 200 °C | Operating temperature max. |

Calculation factors

|                |      |                                                                                  |
|----------------|------|----------------------------------------------------------------------------------|
| e              | 0,34 | Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y |
| Y <sub>1</sub> | 2    | Dynamic axial load factor                                                        |
| Y <sub>2</sub> | 2,98 | Dynamic axial load factor                                                        |
| Y <sub>0</sub> | 1,96 | Static axial load factor                                                         |