



FAG

22317-E1A-XL-K-M

Spherical Roller Bearing

Spherical roller bearing 223...-E1A-XL-K-M,
symmetric 2 outer ribs

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E1A	Without central rip
Bore type	K	Tapered, taper 1:12
Cage	M	Brass Cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication	Standard	

Main Dimensions & Performance Data

d	85 mm	Bore diameter
D	180 mm	Outside diameter
B	60 mm	Width
C _r	540.000 N	Basic dynamic load rating, radial
C _{0r}	560.000 N	Basic static load rating, radial
C _{ur}	51.000 N	Fatigue load limit, radial
n _G	4.100 1/min	Limiting speed
n _{gr}	3.200 1/min	Reference speed
≈m	6,997 kg	Masa



Mounting dimensions

d _{a min}	99 mm	Minimum diameter shaft shoulder
D _{a max}	166 mm	Maximum diameter of housing shoulder
r _{a max}	2,5 mm	Maximum recess radius
d _{a max}	104 mm	Maximum diameter of shaft shoulder
d _{b min}	94 mm	Minimum cavity diameter of the sleeve
B _{a min}	6 mm	Minimum cavity width of the sleeve

Dimensions

r _{min}	3 mm	Minimum chamfer dimension
D ₁	154,2 mm	Bore diameter outer ring
d ₂	104,4 mm	Raceway diameter of the inner ring
d _s	4,8 mm	Diameter lubrication hole
n _s	9,5 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,33	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	2,04	Dynamic axial load factor
Y ₂	3,04	Dynamic axial load factor
Y ₀	2	Static axial load factor

Additional information

H2317	Adapter sleeve
AHX2317	Withdrawal sleeve