

**FAG****22318-E1A-XL-K-MA-T41A** **Spherical Roller Bearing**

Spherical roller bearing 223...-E1A-XL-K-MA-T41A, symmetric 2 outer ribs

**X-life****Informacje techniczne****Twoja aktualna wersja produktu**

|                                                |              |                                   |
|------------------------------------------------|--------------|-----------------------------------|
| Design                                         | E1A          | Without central rip               |
| Bore type                                      | K            | Tapered, taper 1:12               |
| Cage                                           | MA           | Solid brass cage                  |
| Radial internal clearance                      | C4 (Group 4) | Internal clearance larger than C3 |
| Relubrication                                  | Standard     |                                   |
| Spherical roller bearing for vibrating screens | T41A         | For vibrating screens             |

**Main Dimensions & Performance Data**

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 90 mm       | Bore diameter                     |
| D               | 190 mm      | Outside diameter                  |
| B               | 64 mm       | Width                             |
| C <sub>r</sub>  | 610.000 N   | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 630.000 N   | Basic static load rating, radial  |
| C <sub>ur</sub> | 56.000 N    | Fatigue load limit, radial        |
| n <sub>G</sub>  | 3.850 1/min | Limiting speed                    |
| n <sub>gr</sub> | 3.000 1/min | Reference speed                   |
| m               | 8,6 kg      | Masa                              |



Mounting dimensions

|                    |        |                                       |
|--------------------|--------|---------------------------------------|
| d <sub>a min</sub> | 104 mm | Minimum diameter shaft shoulder       |
| D <sub>a max</sub> | 176 mm | Maximum diameter of housing shoulder  |
| r <sub>a max</sub> | 2,5 mm | Maximum recess radius                 |
| d <sub>a max</sub> | 110 mm | Maximum diameter of shaft shoulder    |
| d <sub>b min</sub> | 100 mm | Minimum cavity diameter of the sleeve |
| B <sub>a min</sub> | 6 mm   | Minimum cavity width of the sleeve    |

Dimensions

|                  |          |                                    |
|------------------|----------|------------------------------------|
| r <sub>min</sub> | 3 mm     | Minimum chamfer dimension          |
| D <sub>1</sub>   | 162,5 mm | Bore diameter outer ring           |
| d <sub>2</sub>   | 110,2 mm | Raceway diameter of the inner ring |
| d <sub>s</sub>   | 6,3 mm   | Diameter lubrication hole          |
| n <sub>s</sub>   | 12,2 mm  | Width of lubricating groove        |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -30 °C | Operating temperature min. |
| T <sub>max</sub> | 200 °C | Operating temperature max. |

Calculation factors

|                |      |                                                                                  |
|----------------|------|----------------------------------------------------------------------------------|
| e              | 0,33 | Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y |
| Y <sub>1</sub> | 2,03 | Dynamic axial load factor                                                        |
| Y <sub>2</sub> | 3,02 | Dynamic axial load factor                                                        |
| Y <sub>0</sub> | 1,98 | Static axial load factor                                                         |

Additional information

|         |                   |
|---------|-------------------|
| H2318   | Adapter sleeve    |
| AHX2318 | Withdrawal sleeve |