



FAG


22348-BEA-XL-MB1-H151B-C3

Spherical Roller Bearing

Spherical roller bearing 223...-BEA-XL-MB1, symmetric 2 outer ribs with rib washer

X-life

Informacje techniczne



Twoja aktualna wersja produktu

|                                      |              |                                        |
|--------------------------------------|--------------|----------------------------------------|
| Design                               | BEA          | With lose center lip ring              |
| Bore type                            | Z            | Cylindrical                            |
| Cage                                 | MB1          | Solid brass cage                       |
| Radial internal clearance            | C3 (Group 3) | Internal clearance larger than CN      |
| Relubrication                        | Standard     |                                        |
| Locating feature, bearing outer ring | H151B        | 2 Locking features, bearing outer ring |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 240 mm      | Bore diameter                     |
| D               | 500 mm      | Outside diameter                  |
| B               | 155 mm      | Width                             |
| C <sub>r</sub>  | 3.200.000 N | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 4.050.000 N | Basic static load rating, radial  |
| C <sub>ur</sub> | 315.000 N   | Fatigue load limit, radial        |
| n <sub>G</sub>  | 1.510 1/min | Limiting speed                    |
| n <sub>gr</sub> | 830 1/min   | Reference speed                   |

|    |           |      |
|----|-----------|------|
| ≈m | 146,35 kg | Masa |
|----|-----------|------|



Mounting dimensions

|                    |        |                                 |
|--------------------|--------|---------------------------------|
| d <sub>a min</sub> | 260 mm | Minimum diameter shaft shoulder |
| D <sub>a max</sub> | 480 mm |                                 |
| r <sub>a max</sub> | 4 mm   | Maximum recess radius           |

Dimensions

|                  |          |                             |
|------------------|----------|-----------------------------|
| r <sub>min</sub> | 5 mm     | Minimum chamfer dimension   |
| D <sub>1</sub>   | 426,4 mm | Bore diameter outer ring    |
| d <sub>s</sub>   | 12,5 mm  | Diameter lubrication hole   |
| n <sub>s</sub>   | 23,5 mm  | Width of lubricating groove |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -30 °C | Operating temperature min. |
| T <sub>max</sub> | 200 °C | Operating temperature max. |

Calculation factors

|                |      |                           |
|----------------|------|---------------------------|
| e              | 0,32 |                           |
| Y <sub>1</sub> | 2,12 | Dynamic axial load factor |
| Y <sub>2</sub> | 3,15 | Dynamic axial load factor |
| Y <sub>0</sub> | 2,07 | Static axial load factor  |



### Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna