



FAG

22352-BEA-XL-K-MB1-C4

Spherical Roller Bearing

Spherical roller bearing 223...-BEA-XL-K-MB1, symmetric 2 outer ribs with rib washer

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	BEA	With lose center lip ring
Bore type	K	Tapered, taper 1:12
Cage	MB1	Solid brass cage
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Relubrication	Standard	

Main Dimensions & Performance Data

d	260 mm	Bore diameter
D	540 mm	Outside diameter
B	165 mm	Width
C _r	3.650.000 N	Basic dynamic load rating, radial
C _{0r}	4.650.000 N	Basic static load rating, radial
C _{ur}	360.000 N	Fatigue load limit, radial
n _G	1.390 1/min	Limiting speed
n _{gr}	740 1/min	Reference speed
≈m	177,6 kg	Masa



Mounting dimensions

$d_{a \min}$	286 mm	Minimum diameter shaft shoulder
$D_{a \max}$	514 mm	
$r_{a \max}$	5 mm	Maximum recess radius
$d_{a \max}$	322 mm	
$d_{b \min}$	278 mm	Minimum cavity diameter of the sleeve
$B_{a \min}$	11 mm	Minimum cavity width of the sleeve

Dimensions

$r_{\min}$	6 mm	Minimum chamfer dimension
D_1	460,6 mm	Bore diameter outer ring
d_s	12,5 mm	Diameter lubrication hole
n_s	23,5 mm	Width of lubricating groove

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

Calculation factors

e	0,31	
Y_1	2,15	Dynamic axial load factor
Y_2	3,2	Dynamic axial load factor
Y_0	2,1	Static axial load factor

Additional information

H2352X	Adapter sleeve
AH2352G	Withdrawal sleeve



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna