



FAG



23022-E1A-XL-K-M-C3

Spherical Roller Bearing

Spherical roller bearings 230...-E1A-K, main dimensions to DIN 635-2, with tapered bore, taper 1:12

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E1A	Without central rip
Bore type	K	Tapered, taper 1:12
Cage	M	Brass Cage
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Relubrication	Standard	
Special material	Standard	

Main Dimensions & Performance Data

d	110 mm	Bore diameter
D	170 mm	Outside diameter
B	45 mm	Width
C _r	400.000 N	Basic dynamic load rating, radial
C _{0r}	530.000 N	Basic static load rating, radial
C _{ur}	54.000 N	Fatigue load limit, radial
n _G	4.200 1/min	Limiting speed
n _{gr}	3.000 1/min	Reference speed

≈m	3,57 kg	Masa
----	---------	------



Mounting dimensions

d _{a min}	118,8 mm	Minimum diameter shaft shoulder
D _{a max}	161,2 mm	Maximum diameter of housing shoulder
r _{a max}	2 mm	Maximum recess radius
d _{a max}	123 mm	Maximum diameter of shaft shoulder
d _{b min}	118 mm	Minimum cavity diameter of the sleeve
B _{a min}	14 mm	Minimum cavity width of the sleeve

Dimensions

r _{min}	2 mm	Minimum chamfer dimension
D ₁	154,6 mm	Bore diameter outer ring
d _s	3,2 mm	Diameter lubrication hole
n _s	6,5 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,23	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	2,9	Dynamic axial load factor
Y ₂	4,31	Dynamic axial load factor
Y ₀	2,83	Static axial load factor

Additional information

H322	Adapter sleeve
AHX322	Withdrawal sleeve



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna