





FAG

23052-BE-XL-H151B [🔗](#)
Spherical Roller Bearing

Spherical roller bearings 230...-E1, main dimensions to DIN 635-2

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	BE	With lose center lip ring
Bore type	Z	Cylindrical
Cage	JPB	Sheet metal cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication	Standard	
Locating feature, bearing outer ring	H151B	2 Locking features, bearing outer ring

Main Dimensions & Performance Data

d	260 mm	Bore diameter
D	400 mm	Outside diameter
B	104 mm	Width
C _r	1.670.000 N	Basic dynamic load rating, radial
C _{0r}	2.600.000 N	Basic static load rating, radial
C _{ur}	239.000 N	Fatigue load limit, radial
n _G	1.850 1/min	Limiting speed
n _{gr}	1.170 1/min	Reference speed

≈m	46,6 kg	Masa
----	---------	------



Mounting dimensions

$d_{a\ min}$	274,6 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	385,4 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	3 mm	Maximum recess radius

Dimensions

$r_{\ min}$	4 mm	Minimum chamfer dimension
D_1	358,7 mm	Bore diameter outer ring
d_2	295,5 mm	Raceway diameter of the inner ring
d_s	9,5 mm	Diameter lubrication hole
n_s	17,7 mm	Width of lubricating groove

Temperature range

$T_{\ min}$	-30 °C	Operating temperature min.
$T_{\ max}$	200 °C	Operating temperature max.

Calculation factors

e	0,23	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	2,9	Dynamic axial load factor
Y_2	4,31	Dynamic axial load factor
Y_0	2,83	Static axial load factor



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna