



FAG

23068-BEA-XL-MB1-H40

Spherical Roller Bearing

Spherical roller bearing 230...-BEA-XL-MB1-H40, symmetric 2 outer ribs with rib washer

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	BEA	With lose center lip ring
Bore type	Z	Cylindrical
Cage	MB1	Solid brass cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication	H40	Without lubricating groove and holes

Main Dimensions & Performance Data

d	340 mm	Bore diameter
D	520 mm	Outside diameter
B	133 mm	Width
C _r	2.700.000 N	Basic dynamic load rating, radial
C _{0r}	4.400.000 N	Basic static load rating, radial
C _{ur}	375.000 N	Fatigue load limit, radial
n _G	1.360 1/min	Limiting speed
n _{gr}	840 1/min	Reference speed
≈m	101,46 kg	Masa

Mounting dimensions

d _{a min}	358 mm	Minimum diameter shaft shoulder
D _{a max}	502 mm	
r _{a max}	4 mm	Maximum recess radius



Dimensions

r_{min} 5 mm Minimum chamfer dimension

D_1 467,1 mm Bore diameter outer ring

Temperature range

T_{min} -30 °C Operating temperature min.

T_{max} 200 °C Operating temperature max.

Calculation factors

e 0,23

Y_1 2,92 Dynamic axial load factor

Y_2 4,35 Dynamic axial load factor

Y_0 2,86 Static axial load factor

Właściwości

 F_r Obciążenie promieniowe

 F_a Obciążenie osiowe jednokierunkowe

 F_a Obciążenie osiowe dwukierunkowe

 Smarowanie smarem

 Smarowanie olejem

 Bez uszczelnienia

 Nieosiowość statyczna

 Nieosiowość dynamiczna