



FAG

**23072-BEA-XL-K-MB1-T52BW-C3**

## Spherical Roller Bearing

Spherical roller bearing 230...-BEA-XL-K-MB1,  
symmetric 2 outer ribs with rib washer

X-life

## Informacje techniczne



## Twoja aktualna wersja produktu

|                           |              |                                   |
|---------------------------|--------------|-----------------------------------|
| Design                    | BEA          | With lose center lip ring         |
| Bore type                 | K            | Tapered, taper 1:12               |
| Cage                      | MB1          | Solid brass cage                  |
| Radial internal clearance | C3 (Group 3) | Internal clearance larger than CN |
| Relubrication             | Standard     |                                   |

## Main Dimensions &amp; Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 360 mm      | Bore diameter                     |
| D               | 540 mm      | Outside diameter                  |
| B               | 134 mm      | Width                             |
| C <sub>r</sub>  | 2.800.000 N | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 4.650.000 N | Basic static load rating, radial  |
| C <sub>ur</sub> | 400.000 N   | Fatigue load limit, radial        |
| n <sub>G</sub>  | 1.300 1/min | Limiting speed                    |
| n <sub>gr</sub> | 790 1/min   | Reference speed                   |
| ≈m              | 103,2 kg    | Masa                              |



### Mounting dimensions

|              |        |                                       |
|--------------|--------|---------------------------------------|
| $d_{a \min}$ | 378 mm | Minimum diameter shaft shoulder       |
| $D_{a \max}$ | 522 mm |                                       |
| $r_{a \max}$ | 4 mm   | Maximum recess radius                 |
| $d_{a \max}$ | 402 mm |                                       |
| $d_{b \min}$ | 375 mm | Minimum cavity diameter of the sleeve |
| $B_{a \min}$ | 14 mm  | Minimum cavity width of the sleeve    |

### Dimensions

|            |          |                             |
|------------|----------|-----------------------------|
| $r_{\min}$ | 5 mm     | Minimum chamfer dimension   |
| $D_1$      | 487,6 mm | Bore diameter outer ring    |
| $d_s$      | 12,5 mm  | Diameter lubrication hole   |
| $n_s$      | 23,5 mm  | Width of lubricating groove |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 200 °C | Operating temperature max. |

### Calculation factors

|       |      |                           |
|-------|------|---------------------------|
| $e$   | 0,22 |                           |
| $Y_1$ | 3,04 | Dynamic axial load factor |
| $Y_2$ | 4,53 | Dynamic axial load factor |
| $Y_0$ | 2,97 | Static axial load factor  |

### Additional information

|           |                   |
|-----------|-------------------|
| H3072-HG  | Adapter sleeve    |
| AH3072G-H | Withdrawal sleeve |



### Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna