



FAG

23092-BEA-XL-K-MB1-T52BW-C3

Spherical Roller Bearing

Spherical roller bearing 230...-BEA-XL-K-MB1, symmetric 2 outer ribs with rib washer

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	BEA	With lose center lip ring
Bore type	K	Tapered, taper 1:12
Cage	MB1	Solid brass cage
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Relubrication	Standard	

Main Dimensions & Performance Data

d	460 mm	Bore diameter
D	680 mm	Outside diameter
B	163 mm	Width
C _r	4.300.000 N	Basic dynamic load rating, radial
C _{0r}	7.500.000 N	Basic static load rating, radial
C _{ur}	610.000 N	Fatigue load limit, radial
n _G	980 1/min	Limiting speed
n _{gr}	580 1/min	Reference speed
≈m	196,5 kg	Masa



Mounting dimensions

d _{a min}	483 mm	Minimum diameter shaft shoulder
D _{a max}	657 mm	
r _{a max}	5 mm	Maximum recess radius
d _{a max}	509 mm	
d _{b min}	478 mm	Minimum cavity diameter of the sleeve
B _{a min}	17 mm	Minimum cavity width of the sleeve

Dimensions

r _{min}	6 mm	Minimum chamfer dimension
D ₁	616,7 mm	Bore diameter outer ring
d _s	12,5 mm	Diameter lubrication hole
n _s	23,5 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,21	
Y ₁	3,17	Dynamic axial load factor
Y ₂	4,72	Dynamic axial load factor
Y ₀	3,1	Static axial load factor

Additional information

H3092-HG	Adapter sleeve
AHX3092G-H	Withdrawal sleeve



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna