



FAG

231/530-BEA-XL-MB1-H40

Spherical Roller Bearing

Spherical roller bearing 231...-BEA-XL-MB1-H40, symmetric 2 outer ribs with rib washer

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	BEA	With lose center lip ring
Bore type	Z	Cylindrical
Cage	MB1	Solid brass cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication	H40	Without lubricating groove and holes

Main Dimensions & Performance Data

d	530 mm	Bore diameter
D	870 mm	Outside diameter
B	272 mm	Width
C _r	8.900.000 N	Basic dynamic load rating, radial
C _{0r}	15.000.000 N	Basic static load rating, radial
C _{ur}	960.000 N	Fatigue load limit, radial
n _G	660 1/min	Limiting speed
n _{gr}	325 1/min	Reference speed
≈m	628 kg	Masa

Mounting dimensions

d _{a min}	562 mm	Minimum diameter shaft shoulder
D _{a max}	838 mm	
r _{a max}	6 mm	Maximum recess radius



Dimensions

r _{min}	7,5 mm	Minimum chamfer dimension
D ₁	760,5 mm	Bore diameter outer ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,3	
Y ₁	2,25	Dynamic axial load factor
Y ₂	3,34	Dynamic axial load factor
Y ₀	2,2	Static axial load factor

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Nieosiowość statyczna
	Nieosiowość dynamiczna