



FAG

2312-TVH-C3>N

Self-aligning ball bearing

Self-aligning ball bearing 23..-TVH, plastic cage

Informacje techniczne



Twoja aktualna wersja produktu

Version code	>N	Not marked on bearing
Bore type	Z	Cylindrical
Sealing	Without	Not sealed
Cage	TVH	Solid cage made of glass-fiber reinforced polyamide PA66
Tolerance class	PN	Normal (ISO 492:2023)
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	60 mm	Bore diameter
D	130 mm	Outside diameter
B	46 mm	Width
C _r	89.000 N	Basic dynamic load rating, radial
C _{0r}	28.000 N	Basic static load rating, radial
C _{ur}	1.790 N	Fatigue load limit, radial
n _G	5.200 1/min	Limiting speed
n _{gr}	6.700 1/min	Reference speed
m	2,53 kg	Masa



Mounting dimensions

$d_{a\ min}$	72 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	118 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	2,1 mm	Maximum fillet radius

Dimensions

$r_{\ min}$	2,1 mm	Minimum chamfer dimension
D_1	108,54 mm	Shoulder diameter outer ring
d_1	76,95 mm	Shoulder diameter inner ring

Temperature range

$T_{\ min}$	-30 °C	Operating temperature min.
$T_{\ max}$	120 °C	Operating temperature max.

Calculation factors

e	0,41	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	1,55	Dynamic axial load factor
Y_2	2,39	Dynamic axial load factor
Y_0	1,62	Static axial load factor

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Nieosiowość statyczna
	Nieosiowość dynamiczna