





FAG

2319-K-M-C3>J

Self-aligning ball bearing

Self-aligning ball bearing 23..-K-M, tapered bore taper 1:12, solid brass cage

Informacje techniczne

Twoja aktualna wersja produktu

Version code	>J	Not marked on bearing
Bore type	K	Tapered, taper 1:12
Sealing	Without	Not sealed
Cage	M	Solid brass cage, ball guided
Tolerance class	PN	Normal (ISO 492:2023)
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	95 mm	Bore diameter
D	200 mm	Outside diameter
B	67 mm	Width
C _r	167.000 N	Basic dynamic load rating, radial
C _{0r}	64.000 N	Basic static load rating, radial
C _{ur}	3.350 N	Fatigue load limit, radial
n _G	4.800 1/min	Limiting speed
n _{gr}	4.750 1/min	Reference speed
≈m	9,65 kg	Masa



Mounting dimensions

$d_{a \min}$	109 mm	Minimum diameter shaft shoulder
$d_{a \max}$	117 mm	Maximum diameter shaft shoulder
$D_{a \max}$	186 mm	Maximum diameter of housing shoulder
$d_{b \min}$	105 mm	Minimum cavity diameter of the sleeve
$B_{a \min}$	7 mm	Minimum cavity width of the sleeve
$r_{a \max}$	2,5 mm	Maximum fillet radius

Dimensions

$r_{\min}$	3 mm	Minimum chamfer dimension
D_1	167,65 mm	Shoulder diameter outer ring
d_1	121,6 mm	Shoulder diameter inner ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

Calculation factors

e	0,38	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	1,66	Dynamic axial load factor
Y_2	2,57	Dynamic axial load factor
Y_0	1,74	Static axial load factor

Additional information

H2319

Adapter sleeve



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna