



FAG

2319-K-M>J

Self-aligning ball bearing

Self-aligning ball bearing 23..-K-M, tapered bore taper 1:12, solid brass cage






Informacje techniczne

Twoja aktualna wersja produktu

Version code	>J	Not marked on bearing
Bore type	K	Tapered, taper 1:12
Sealing	Without	Not sealed
Cage	M	Solid brass cage, ball guided
Tolerance class	PN	Normal (ISO 492:2023)
Radial internal clearance	CN (Group N)	Normal internal clearance
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	95 mm	Bore diameter
D	200 mm	Outside diameter
B	67 mm	Width
C _r	167.000 N	Basic dynamic load rating, radial
C _{0r}	64.000 N	Basic static load rating, radial
C _{ur}	3.350 N	Fatigue load limit, radial
n _G	4.800 1/min	Limiting speed
n _{gr}	4.750 1/min	Reference speed
≈m	9,65 kg	Masa





Mounting dimensions

d _{a min}	109 mm	Minimum diameter shaft shoulder
d _{a max}	117 mm	Maximum diameter shaft shoulder
D _{a max}	186 mm	Maximum diameter of housing shoulder
d _{b min}	105 mm	Minimum cavity diameter of the sleeve
B _{a min}	7 mm	Minimum cavity width of the sleeve
r _{a max}	2,5 mm	Maximum fillet radius

Dimensions

r _{min}	3 mm	Minimum chamfer dimension
D ₁	167,65 mm	Shoulder diameter outer ring
d ₁	121,6 mm	Shoulder diameter inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Calculation factors

e	0,38	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	1,66	Dynamic axial load factor
Y ₂	2,57	Dynamic axial load factor
Y ₀	1,74	Static axial load factor

Additional information

H2319	Adapter sleeve
-------	----------------



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Nieosiowość statyczna



Nieosiowość dynamiczna