



FAG


23238-BE-XL-H151B

Spherical Roller Bearing

Spherical roller bearing 232...-BE-XL,
symmetric with rib washer

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	BE	With lose center lip ring
Bore type	Z	Cylindrical
Cage	JPB	Sheet metal cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication	Standard	
Locating feature, bearing outer ring	H151B	2 Locking features, bearing outer ring

Main Dimensions & Performance Data

d	190 mm	Bore diameter
D	340 mm	Outside diameter
B	120 mm	Width
C _r	1.740.000 N	Basic dynamic load rating, radial
C _{0r}	2.400.000 N	Basic static load rating, radial
C _{ur}	206.000 N	Fatigue load limit, radial
n _G	1.990 1/min	Limiting speed
n _{gr}	1.070 1/min	Reference speed
≈m	46,195 kg	Masa



Mounting dimensions

$d_{a\ min}$	207 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	323 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	3 mm	Maximum recess radius

Dimensions

$r_{\min}$	4 mm	Minimum chamfer dimension
D_1	289 mm	Bore diameter outer ring
d_2	222,4 mm	Raceway diameter of the inner ring
d_s	9,5 mm	Diameter lubrication hole
n_s	17,7 mm	Width of lubricating groove

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

Calculation factors

e	0,34	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	1,98	Dynamic axial load factor
Y_2	2,94	Dynamic axial load factor
Y_0	1,93	Static axial load factor



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna