



FAG

23256-BEA-XL-K-MB1-H40

Spherical Roller Bearing

Spherical roller bearing 232...-BEA-XL-K-MB1-H40, symmetric 2 outer ribs with rib washer

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	BEA	With lose center lip ring
Bore type	K	Tapered, taper 1:12
Cage	MB1	Solid brass cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication	H40	Without lubricating groove and holes

Main Dimensions & Performance Data

d	280 mm	Bore diameter
D	500 mm	Outside diameter
B	176 mm	Width
C _r	3.550.000 N	Basic dynamic load rating, radial
C _{0r}	5.200.000 N	Basic static load rating, radial
C _{ur}	395.000 N	Fatigue load limit, radial
n _G	1.280 1/min	Limiting speed
n _{gr}	630 1/min	Reference speed
≈m	144,385 kg	Masa



Mounting dimensions

d _{a min}	300 mm	Minimum diameter shaft shoulder
D _{a max}	480 mm	
r _{a max}	4 mm	Maximum recess radius
d _{a max}	329 mm	
d _{b min}	299 mm	Minimum cavity diameter of the sleeve
B _{a min}	11 mm	Minimum cavity width of the sleeve

Dimensions

r _{min}	5 mm	Minimum chamfer dimension
D ₁	425,4 mm	Bore diameter outer ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,34	
Y ₁	1,96	Dynamic axial load factor
Y ₂	2,92	Dynamic axial load factor
Y ₀	1,92	Static axial load factor

Additional information

H2356X	Adapter sleeve
AH2356G	Withdrawal sleeve



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna