



FAG

23268-BEA-XL-K-MB1-C3

Spherical Roller Bearing

Spherical roller bearing 232...-BEA-XL-K-MB1, symmetric 2 outer ribs with rib washer

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	BEA	With lose center lip ring
Bore type	K	Tapered, taper 1:12
Cage	MB1	Solid brass cage
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Relubrication	Standard	

Main Dimensions & Performance Data

d	340 mm	Bore diameter
D	620 mm	Outside diameter
B	224 mm	Width
C _r	5.300.000 N	Basic dynamic load rating, radial
C _{0r}	7.900.000 N	Basic static load rating, radial
C _{ur}	580.000 N	Fatigue load limit, radial
n _G	1.000 1/min	Limiting speed
n _{gr}	475 1/min	Reference speed
≈m	286 kg	Masa



Mounting dimensions

d _{a min}	366 mm	Minimum diameter shaft shoulder
D _{a max}	594 mm	
r _{a max}	5 mm	Maximum recess radius
d _{a max}	402 mm	
d _{b min}	364 mm	Minimum cavity diameter of the sleeve
B _{a min}	14 mm	Minimum cavity width of the sleeve

Dimensions

r _{min}	6 mm	Minimum chamfer dimension
D ₁	523,5 mm	Bore diameter outer ring
d _s	12,5 mm	Diameter lubrication hole
n _s	23,5 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,36	
Y ₁	1,85	Dynamic axial load factor
Y ₂	2,76	Dynamic axial load factor
Y ₀	1,81	Static axial load factor

Additional information

H3268-HG	Adapter sleeve
AH3268G-H	Withdrawal sleeve



Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Łożysko gabarytowe
	Nieosiowość statyczna
	Nieosiowość dynamiczna