

**FAG****234412-M-SP** [🔗](#)

Axial angular contact ball bearing

Axial angular contact ball bearings 2344,
double direction, separable, restricted
tolerances

Informacje techniczne



Twoja aktualna wersja produktu

Cage	M	Brass Cage
Tolerance class	SP	Tolerance class SP

Main Dimensions & Performance Data

d	60 mm	Bore diameter
D	95 mm	Outside diameter
B	44 mm	Width
C	22 mm	Width, outer ring
C _a	37.000 N	Basic dynamic load rating, axial
C _{0a}	102.000 N	Basic static load rating, axial
C _{ua}	9.400 N	Fatigue load limit, axial
n _G Grease	6.000 1/min	Limiting speed for grease lubrication
n _G Oil	8.000 1/min	Limiting speed for oil lubrication
≈m	1,011 kg	Masa



Mounting dimensions

d _a	74 mm	Diameter shaft shoulder
d _a	h12	Diameter shaft shoulder clearance
D _a	89,5 mm	Shoulder diameter outer ring
D _a	H12	Shoulder diameter outer ring clearance
r _{a max}	1,1 mm	Maximum recess radius
r _{a1 max}	0,3 mm	Maximum recess radius
α	60 °	Contact angle
a	158,5 mm	Distance between the apexes of the pressure cones

Dimensions

d ₁	83 mm	Rip diameter shaft washer
B ₁	11 mm	Height wave disc
r _{min}	1,1 mm	Minimum chamfer dimension
r _{1 min}	0,3 mm	Minimum chamfer dimension
d _s	3,2 mm	Diameter lubrication hole
n _s	6,5 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Additional information

c _a	455 N/μm	Axial rigidity
K _{aE}	728 N	Lift-off force
F _v	255 N	Preload force



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia