

**FAG****234415-M-SP** [🔗](#)

Axial angular contact ball bearing

Axial angular contact ball bearings 2344,
double direction, separable, restricted
tolerances

Informacje techniczne



Twoja aktualna wersja produktu

Cage	M	Brass Cage
Tolerance class	SP	Tolerance class SP

Main Dimensions & Performance Data

d	75 mm	Bore diameter
D	115 mm	Outside diameter
B	48 mm	Width
C	24 mm	Width, outer ring
C _a	47.500 N	Basic dynamic load rating, axial
C _{0a}	144.000 N	Basic static load rating, axial
C _{ua}	13.300 N	Fatigue load limit, axial
n _G Grease	5.000 1/min	Limiting speed for grease lubrication
n _G Oil	6.700 1/min	Limiting speed for oil lubrication
≈m	1,578 kg	Masa



Mounting dimensions

d _a	91,5 mm	Diameter shaft shoulder
d _a	h12	Diameter shaft shoulder clearance
D _a	108,5 mm	Shoulder diameter outer ring
D _a	H12	Shoulder diameter outer ring clearance
r _a max	1,1 mm	Maximum recess radius
r _{a1} max	0,3 mm	Maximum recess radius
α	60 °	Contact angle
a	191,5 mm	Distance between the apexes of the pressure cones

Dimensions

d ₁	102 mm	Rip diameter shaft washer
B ₁	12 mm	Height wave disc
r _{min}	1,1 mm	Minimum chamfer dimension
r ₁ min	0,3 mm	Minimum chamfer dimension
d _s	3,2 mm	Diameter lubrication hole
n _s	6,5 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Additional information

c _a	589 N/μm	Axial rigidity
K _{aE}	969 N	Lift-off force
F _v	340 N	Preload force



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia