




FAG

23860-MB-C3

Spherical Roller Bearing

Spherical roller bearing 238...-MB, symmetric
3 ribs

Informacje techniczne



Twoja aktualna wersja produktu

Bore type	Z	Cylindrical
Cage	MB	Solid brass cage
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Relubrication	Standard	

Main Dimensions & Performance Data

d	300 mm	Bore diameter
D	380 mm	Outside diameter
B	60 mm	Width
C _r	620.000 N	Basic dynamic load rating, radial
C _{0r}	1.460.000 N	Basic static load rating, radial
C _{ur}	103.000 N	Fatigue load limit, radial
n _G	2.120 1/min	Limiting speed
n _{gr}	1.030 1/min	Reference speed

≈m 16,485 kg Masa

Mounting dimensions

d _{a min}	310,2 mm	Minimum diameter shaft shoulder
D _{a max}	369,8 mm	Maximum diameter of housing shoulder
r _{a max}	2,1 mm	Maximum recess radius



Dimensions

r _{min}	2,1 mm	Minimum chamfer dimension
D ₁	357,8 mm	Bore diameter outer ring
d _s	4,8 mm	Diameter lubrication hole
n _s	9,5 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,14	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	4,82	Dynamic axial load factor
Y ₂	7,18	Dynamic axial load factor
Y ₀	4,71	Static axial load factor

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Nieosiowość statyczna
	Nieosiowość dynamiczna