



FAG

23952-MB-C2

Spherical Roller Bearing

Spherical roller bearing 239...-MB, symmetric  
3 ribs

Informacje techniczne



Twoja aktualna wersja produktu

|                           |              |                                    |
|---------------------------|--------------|------------------------------------|
| Bore type                 | Z            | Cylindrical                        |
| Cage                      | MB           | Solid brass cage                   |
| Radial internal clearance | C2 (Group 2) | Internal clearance smaller than CN |
| Relubrication             | Standard     |                                    |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 260 mm      | Bore diameter                     |
| D               | 360 mm      | Outside diameter                  |
| B               | 75 mm       | Width                             |
| C <sub>r</sub>  | 940.000 N   | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 1.940.000 N | Basic static load rating, radial  |
| C <sub>ur</sub> | 111.000 N   | Fatigue load limit, radial        |
| n <sub>G</sub>  | 2.100 1/min | Limiting speed                    |
| n <sub>gr</sub> | 1.190 1/min | Reference speed                   |

≈m 23,3 kg Masa

Mounting dimensions

|                    |          |                                      |
|--------------------|----------|--------------------------------------|
| d <sub>a min</sub> | 270,2 mm | Minimum diameter shaft shoulder      |
| D <sub>a max</sub> | 349,8 mm | Maximum diameter of housing shoulder |
| r <sub>a max</sub> | 2,1 mm   | Maximum recess radius                |



Dimensions

|                  |          |                             |
|------------------|----------|-----------------------------|
| r <sub>min</sub> | 2,1 mm   | Minimum chamfer dimension   |
| D <sub>1</sub>   | 330,5 mm | Bore diameter outer ring    |
| d <sub>s</sub>   | 8 mm     | Diameter lubrication hole   |
| n <sub>s</sub>   | 15 mm    | Width of lubricating groove |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -30 °C | Operating temperature min. |
| T <sub>max</sub> | 200 °C | Operating temperature max. |

Calculation factors

|                |      |                                                                                  |
|----------------|------|----------------------------------------------------------------------------------|
| e              | 0,19 | Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y |
| Y <sub>1</sub> | 3,54 | Dynamic axial load factor                                                        |
| Y <sub>2</sub> | 5,27 | Dynamic axial load factor                                                        |
| Y <sub>0</sub> | 3,46 | Static axial load factor                                                         |

Właściwości

|                                                                                     |                                   |
|-------------------------------------------------------------------------------------|-----------------------------------|
|  | Obciążenie promieniowe            |
|  | Obciążenie osiowe jednokierunkowe |
|  | Obciążenie osiowe dwukierunkowe   |
|  | Smarowanie smarem                 |
|  | Smarowanie olejem                 |
|  | Bez uszczelnienia                 |
|  | Łożysko gabarytowe                |
|  | Nieosiowość statyczna             |
|  | Nieosiowość dynamiczna            |