




FAG

23956-K-MB

Spherical Roller Bearing

Spherical roller bearing 239...-K-MB,  
symmetric 3 ribs

Informacje techniczne



Twoja aktualna wersja produktu

|                           |              |                           |
|---------------------------|--------------|---------------------------|
| Bore type                 | K            | Tapered, taper 1:12       |
| Cage                      | MB           | Solid brass cage          |
| Radial internal clearance | CN (Group N) | Normal internal clearance |
| Relubrication             | Standard     |                           |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 280 mm      | Bore diameter                     |
| D               | 380 mm      | Outside diameter                  |
| B               | 75 mm       | Width                             |
| C <sub>r</sub>  | 970.000 N   | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 2.040.000 N | Basic static load rating, radial  |
| C <sub>ur</sub> | 133.000 N   | Fatigue load limit, radial        |
| n <sub>G</sub>  | 2.000 1/min | Limiting speed                    |
| n <sub>gr</sub> | 1.100 1/min | Reference speed                   |

|    |           |      |
|----|-----------|------|
| ≈m | 23,955 kg | Masa |
|----|-----------|------|



Mounting dimensions

|                    |          |                                       |
|--------------------|----------|---------------------------------------|
| d <sub>a min</sub> | 290,2 mm | Minimum diameter shaft shoulder       |
| D <sub>a max</sub> | 369,8 mm | Maximum diameter of housing shoulder  |
| r <sub>a max</sub> | 2,1 mm   | Maximum recess radius                 |
| d <sub>a max</sub> | 303 mm   | Maximum diameter of shaft shoulder    |
| d <sub>b min</sub> | 290 mm   | Minimum cavity diameter of the sleeve |
| B <sub>a min</sub> | 12 mm    | Minimum cavity width of the sleeve    |

Dimensions

|                  |        |                             |
|------------------|--------|-----------------------------|
| r <sub>min</sub> | 2,1 mm | Minimum chamfer dimension   |
| D <sub>1</sub>   | 350 mm | Bore diameter outer ring    |
| d <sub>s</sub>   | 8 mm   | Diameter lubrication hole   |
| n <sub>s</sub>   | 15 mm  | Width of lubricating groove |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -30 °C | Operating temperature min. |
| T <sub>max</sub> | 200 °C | Operating temperature max. |

Calculation factors

|                |      |                                                                                  |
|----------------|------|----------------------------------------------------------------------------------|
| e              | 0,18 | Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y |
| Y <sub>1</sub> | 3,76 | Dynamic axial load factor                                                        |
| Y <sub>2</sub> | 5,59 | Dynamic axial load factor                                                        |
| Y <sub>0</sub> | 3,67 | Static axial load factor                                                         |

Additional information

|         |                   |
|---------|-------------------|
| H3956   | Adapter sleeve    |
| AH3956G | Withdrawal sleeve |



## Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna