




FAG

23960-B-K-MB-C4

Spherical Roller Bearing

Spherical roller bearings 239...-K, main dimensions to DIN 635-2, with tapered bore, taper 1:12

Informacje techniczne



Twoja aktualna wersja produktu

Design	B	With fixed central rib
Bore type	K	Tapered, taper 1:12
Cage	MB	Solid brass cage
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Relubrication	Standard	

Main Dimensions & Performance Data

d	300 mm	Bore diameter
D	420 mm	Outside diameter
B	90 mm	Width
C _r	1.270.000 N	Basic dynamic load rating, radial
C _{0r}	2.650.000 N	Basic static load rating, radial
C _{ur}	170.000 N	Fatigue load limit, radial
n _G	1.780 1/min	Limiting speed
n _{gr}	1.000 1/min	Reference speed
≈m	37,8 kg	Masa



Mounting dimensions

d _{a min}	312,4 mm	Minimum diameter shaft shoulder
D _{a max}	407,6 mm	Maximum diameter of housing shoulder
r _{a max}	2,5 mm	Maximum recess radius
d _{a max}	329 mm	Maximum diameter of shaft shoulder
d _{b min}	311 mm	Minimum cavity diameter of the sleeve
B _{a min}	12 mm	Minimum cavity width of the sleeve

Dimensions

r _{min}	3 mm	Minimum chamfer dimension
D ₁	384,6 mm	Bore diameter outer ring
d _s	9,5 mm	Diameter lubrication hole
n _s	17,7 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,2	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	3,42	Dynamic axial load factor
Y ₂	5,09	Dynamic axial load factor
Y ₀	3,34	Static axial load factor

Additional information

H3960	Adapter sleeve
AH3960G	Withdrawal sleeve



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna