





FAG

23996-B-K-MB

Spherical Roller Bearing

Spherical roller bearings 239...-K, main dimensions to DIN 635-2, with tapered bore, taper 1:12

Informacje techniczne



Twoja aktualna wersja produktu

Design	B	With fixed central rib
Bore type	K	Tapered, taper 1:12
Cage	MB	Solid brass cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication	Standard	

Main Dimensions & Performance Data

d	480 mm	Bore diameter
D	650 mm	Outside diameter
B	128 mm	Width
C _r	2.550.000 N	Basic dynamic load rating, radial
C _{0r}	6.000.000 N	Basic static load rating, radial
C _{ur}	470.000 N	Fatigue load limit, radial
n _G	1.040 1/min	Limiting speed
n _{gr}	570 1/min	Reference speed
≈m	120 kg	Masa



Mounting dimensions

d _{a min}	498 mm	Minimum diameter shaft shoulder
D _{a max}	632 mm	Maximum diameter of housing shoulder
r _{a max}	4 mm	Maximum recess radius
d _{a max}	523 mm	Maximum diameter of shaft shoulder
d _{b min}	496 mm	Minimum cavity diameter of the sleeve
B _{a min}	18 mm	Minimum cavity width of the sleeve

Dimensions

r _{min}	5 mm	Minimum chamfer dimension
D ₁	598,8 mm	Bore diameter outer ring
d _s	12,5 mm	Diameter lubrication hole
n _s	23,5 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,18	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	3,76	Dynamic axial load factor
Y ₂	5,59	Dynamic axial load factor
Y ₀	3,67	Static axial load factor

Additional information

H3996-HG	Adapter sleeve
AH3996-H	Withdrawal sleeve



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna