



FAG



24032-BE-XL-2VSR-H40-C4

Spherical Roller Bearing

Spherical roller bearing 240...-BE-XL-2VSR-H40, symmetric with rib washer

X-life

Informacje techniczne



Twoja aktualna wersja produktu

|                           |              |                                       |
|---------------------------|--------------|---------------------------------------|
| Design                    | BE           | With lose center lip ring             |
| Bore type                 | Z            | Cylindrical                           |
| Cage                      | JPB          | Sheet metal cage                      |
| Radial internal clearance | C4 (Group 4) | Internal clearance larger than C3     |
| Relubrication             | H40          | Without lubricating groove and holes  |
| Sealing                   | 2VSR         | Seals on both sides, high temperature |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 160 mm      | Bore diameter                     |
| D               | 240 mm      | Outside diameter                  |
| B               | 80 mm       | Width                             |
| C <sub>r</sub>  | 770.000 N   | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 1.240.000 N | Basic static load rating, radial  |
| C <sub>ur</sub> | 140.000 N   | Fatigue load limit, radial        |
| n <sub>G</sub>  | 640 1/min   | Limiting speed                    |
| ≈m              | 12,6 kg     | Masa                              |

Mounting dimensions

|                    |          |                                      |
|--------------------|----------|--------------------------------------|
| d <sub>a min</sub> | 170,2 mm | Minimum diameter shaft shoulder      |
| D <sub>a max</sub> | 229,8 mm | Maximum diameter of housing shoulder |
| r <sub>a max</sub> | 2,1 mm   | Maximum recess radius                |



Dimensions

|           |          |                                    |
|-----------|----------|------------------------------------|
| $r_{min}$ | 2,1 mm   | Minimum chamfer dimension          |
| $D_1$     | 226,9 mm | Bore diameter outer ring           |
| $d_2$     | 174,8 mm | Raceway diameter of the inner ring |

Temperature range

|           |        |                            |
|-----------|--------|----------------------------|
| $T_{min}$ | -30 °C | Operating temperature min. |
| $T_{max}$ | 180 °C | Operating temperature max. |

Calculation factors

|       |      |                                                                                      |
|-------|------|--------------------------------------------------------------------------------------|
| $e$   | 0,29 | Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y |
| $Y_1$ | 2,32 | Dynamic axial load factor                                                            |
| $Y_2$ | 3,45 | Dynamic axial load factor                                                            |
| $Y_0$ | 2,26 | Static axial load factor                                                             |

Właściwości

|                                                                                     |                                           |
|-------------------------------------------------------------------------------------|-------------------------------------------|
|  | Obciążenie promieniowe                    |
|  | Obciążenie osiowe jednokierunkowe         |
|  | Obciążenie osiowe dwukierunkowe           |
|  | $L_h$ Smarowanie dożywotnie, bezobsługowe |
|  | Smarowanie smarem                         |
|  | Uszczelnienie dwustronne                  |
|  | Nieosiowość statyczna                     |
|  | Nieosiowość dynamiczna                    |