



FAG


24072-BEA-XL-MB1-C3

Spherical Roller Bearing

Spherical roller bearing 240...-BEA-XL-MB1, symmetric 2 outer ribs with rib washer

X-life

Informacje techniczne



Twoja aktualna wersja produktu

|                           |              |                                   |
|---------------------------|--------------|-----------------------------------|
| Design                    | BEA          | With lose center lip ring         |
| Bore type                 | Z            | Cylindrical                       |
| Cage                      | MB1          | Solid brass cage                  |
| Radial internal clearance | C3 (Group 3) | Internal clearance larger than CN |
| Relubrication             | Standard     |                                   |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 360 mm      | Bore diameter                     |
| D               | 540 mm      | Outside diameter                  |
| B               | 180 mm      | Width                             |
| C <sub>r</sub>  | 3.650.000 N | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 6.600.000 N | Basic static load rating, radial  |
| C <sub>ur</sub> | 570.000 N   | Fatigue load limit, radial        |
| n <sub>G</sub>  | 1.040 1/min | Limiting speed                    |
| n <sub>gr</sub> | 570 1/min   | Reference speed                   |
| ≈m              | 145,18 kg   | Masa                              |

Mounting dimensions

|                    |        |                                 |
|--------------------|--------|---------------------------------|
| d <sub>a min</sub> | 378 mm | Minimum diameter shaft shoulder |
| D <sub>a max</sub> | 522 mm |                                 |
| r <sub>a max</sub> | 4 mm   | Maximum recess radius           |



Dimensions

|           |          |                             |
|-----------|----------|-----------------------------|
| $r_{min}$ | 5 mm     | Minimum chamfer dimension   |
| $D_1$     | 476,4 mm | Bore diameter outer ring    |
| $d_s$     | 9,5 mm   | Diameter lubrication hole   |
| $n_s$     | 17,7 mm  | Width of lubricating groove |

Temperature range

|           |        |                            |
|-----------|--------|----------------------------|
| $T_{min}$ | -30 °C | Operating temperature min. |
| $T_{max}$ | 200 °C | Operating temperature max. |

Calculation factors

|       |      |                           |
|-------|------|---------------------------|
| $e$   | 0,3  |                           |
| $Y_1$ | 2,23 | Dynamic axial load factor |
| $Y_2$ | 3,32 | Dynamic axial load factor |
| $Y_0$ | 2,18 | Static axial load factor  |

Właściwości

|                                                                                     |                                   |
|-------------------------------------------------------------------------------------|-----------------------------------|
|  | Obciążenie promieniowe            |
|  | Obciążenie osiowe jednokierunkowe |
|  | Obciążenie osiowe dwukierunkowe   |
|  | Smarowanie smarem                 |
|  | Smarowanie olejem                 |
|  | Bez uszczelnienia                 |
|  | Łożysko gabarytowe                |
|  | Nieosiowość statyczna             |
|  | Nieosiowość dynamiczna            |