


**FAG****24136-BE-XL-C3**

Spherical Roller Bearing

Spherical roller bearing 241...-BE-XL,
symmetric with rib washer**X-life**

Informacje techniczne



Twoja aktualna wersja produktu

Design	BE	With lose center lip ring
Bore type	Z	Cylindrical
Cage	JPB	Sheet metal cage
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Relubrication	Standard	

Main Dimensions & Performance Data

d	180 mm	Bore diameter
D	300 mm	Outside diameter
B	118 mm	Width
C _r	1.460.000 N	Basic dynamic load rating, radial
C _{0r}	2.170.000 N	Basic static load rating, radial
C _{ur}	208.000 N	Fatigue load limit, radial
n _G	2.000 1/min	Limiting speed
n _{gr}	980 1/min	Reference speed
≈m	33,2 kg	Masa

Mounting dimensions

d _{a min}	194 mm	Minimum diameter shaft shoulder
D _{a max}	286 mm	Maximum diameter of housing shoulder
r _{a max}	2,5 mm	Maximum recess radius



Dimensions

r _{min}	3 mm	Minimum chamfer dimension
D ₁	255,7 mm	Bore diameter outer ring
d ₂	204,8 mm	Raceway diameter of the inner ring
d _s	6,3 mm	Diameter lubrication hole
n _s	12,2 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,36	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	1,86	Dynamic axial load factor
Y ₂	2,77	Dynamic axial load factor
Y ₀	1,82	Static axial load factor

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Nieosiowość statyczna
	Nieosiowość dynamiczna