



FAG

24180-BE-XL-H40

Spherical Roller Bearing

Spherical roller bearing 241...-BE-XL-H40, symmetric with rib washer

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	BE	With lose center lip ring
Bore type	Z	Cylindrical
Cage	JPB	Sheet metal cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication	H40	Without lubricating groove and holes

Main Dimensions & Performance Data

d	400 mm	Bore diameter
D	650 mm	Outside diameter
B	250 mm	Width
C _r	6.200.000 N	Basic dynamic load rating, radial
C _{0r}	10.600.000 N	Basic static load rating, radial
C _{ur}	790.000 N	Fatigue load limit, radial
n _G	800 1/min	Limiting speed
n _{gr}	300 1/min	Reference speed

Mounting dimensions

d _{a min}	426 mm	Minimum diameter shaft shoulder
D _{a max}	624 mm	Maximum diameter of housing shoulder
r _{a max}	5 mm	Maximum recess radius



Dimensions

r _{min}	6 mm	Minimum chamfer dimension
D ₁	556,5 mm	Bore diameter outer ring
d ₂	448,8 mm	Raceway diameter of the inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,37	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	1,82	Dynamic axial load factor
Y ₂	2,7	Dynamic axial load factor
Y ₀	1,78	Static axial load factor

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna