



FAG

24184-BE-XL-K30

Spherical Roller Bearing

Spherical roller bearings 241...-BE-K30, main dimensions to DIN 635-2, with tapered bore, taper 1:30

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	BE	With lose center lip ring
Bore type	K30	Tapered, taper 1:30
Cage	JPB	Sheet metal cage
Relubrication	Standard	

Main Dimensions & Performance Data

d	420 mm	Bore diameter
D	700 mm	Outside diameter
B	280 mm	Width
C _r	7.400.000 N	Basic dynamic load rating, radial
C _{0r}	12.600.000 N	Basic static load rating, radial
C _{ur}	890.000 N	Fatigue load limit, radial
n _G	720 1/min	Limiting speed
n _{gr}	270 1/min	Reference speed
m	419,5 kg	Masa

Mounting dimensions

d _{a min}	446 mm	Minimum diameter shaft shoulder
D _{a max}	674 mm	Maximum diameter of housing shoulder
r _{a max}	5 mm	Maximum recess radius



Dimensions

r _{min}	6 mm	Minimum chamfer dimension
D ₁	592,2 mm	Bore diameter outer ring
d ₂	472,7 mm	Raceway diameter of the inner ring
d _s	12,5 mm	Diameter lubrication hole
n _s	23,5 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,39	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	1,72	Dynamic axial load factor
Y ₂	2,56	Dynamic axial load factor
Y ₀	1,68	Static axial load factor

Additional information

AH24184-H	Withdrawal sleeve
-----------	-------------------



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna