



FAG

29356-E1-XL

Axial spherical roller bearing

Axial spherical roller bearing 293..-E1-XL, no flanging ring



X-life

Informacje techniczne



Twoja aktualna wersja produktu

Heat treatment	Standard	Standard
Locating feature, housing washer	Without	
Cage	JP	Sheet metal cage
Handling thread holes	Without	
Constricted width and inclination variation	Standard	
Test certificate	Without	

Main Dimensions & Performance Data

d	280 mm	Bore diameter
D	440 mm	Outside diameter
T	95 mm	Height
C _a	2.650.000 N	Basic dynamic load rating, axial
C _{0a}	8.800.000 N	Basic static load rating, axial
C _{ua}	980.000 N	Fatigue load limit, axial
n _G	1.460 1/min	Limiting speed
n _{gr}	740 1/min	Reference speed
≈m	48,84 kg	Masa



Mounting dimensions

d _{a min}	355 mm	Minimum diameter shaft shoulder
D _{a max}	394 mm	Maximum diameter of housing shoulder
D _{b min}	450 mm	Minimum bore diameter housing
d _{b max}	305 mm	Maximum distance sleeve
d _{b1 max}	293 mm	Maximum chamfer diameter of distance sleeve
r _{a max}	4 mm	Maximum recess radius
	30 °	Angle of chamfer of the distance sleeve

Dimensions

D ₁	343 mm	Bore diameter housing washer
d ₁	406,5 mm	Rip diameter shaft washer
r _{min}	5 mm	Minimum chamfer dimension
T ₁	45,5 mm	Height of the housing washer
T ₃	62 mm	Height of the shaft washer
T ₅	86,1 mm	Distance shaft washer - cage
A	158 mm	Distance of the center point

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna