



FAG




29436-E1-XL

Axial spherical roller bearing

Axial spherical roller bearing 294..-E1-XL, no flanging ring

X-life

Informacje techniczne



Twoja aktualna wersja produktu

|                                             |          |                  |
|---------------------------------------------|----------|------------------|
| Heat treatment                              | Standard | Standard         |
| Locating feature, housing washer            | Without  |                  |
| Cage                                        | JP       | Sheet metal cage |
| Handling thread holes                       | Without  |                  |
| Constricted width and inclination variation | Standard |                  |
| Test certificate                            | Without  |                  |

Main Dimensions & Performance Data

|                 |             |                                  |
|-----------------|-------------|----------------------------------|
| d               | 180 mm      | Bore diameter                    |
| D               | 360 mm      | Outside diameter                 |
| T               | 109 mm      | Height                           |
| C <sub>a</sub>  | 2.850.000 N | Basic dynamic load rating, axial |
| C <sub>0a</sub> | 7.700.000 N | Basic static load rating, axial  |
| C <sub>ua</sub> | 770.000 N   | Fatigue load limit, axial        |
| n <sub>G</sub>  | 1.860 1/min | Limiting speed                   |
| n <sub>gr</sub> | 940 1/min   | Reference speed                  |
| ≈m              | 45,2 kg     | Masa                             |



Mounting dimensions

|                     |        |                                             |
|---------------------|--------|---------------------------------------------|
| d <sub>a min</sub>  | 265 mm | Minimum diameter shaft shoulder             |
| D <sub>a max</sub>  | 305 mm | Maximum diameter of housing shoulder        |
| D <sub>b min</sub>  | 366 mm | Minimum bore diameter housing               |
| d <sub>b max</sub>  | 210 mm | Maximum distance sleeve                     |
| d <sub>b1 max</sub> | 197 mm | Maximum chamfer diameter of distance sleeve |
| r <sub>a max</sub>  | 4 mm   | Maximum recess radius                       |
|                     | 30 °   | Angle of chamfer of the distance sleeve     |

Dimensions

|                  |          |                              |
|------------------|----------|------------------------------|
| D <sub>1</sub>   | 250 mm   | Bore diameter housing washer |
| d <sub>1</sub>   | 315,5 mm | Rip diameter shaft washer    |
| r <sub>min</sub> | 5 mm     | Minimum chamfer dimension    |
| T <sub>1</sub>   | 53 mm    | Height of the housing washer |
| T <sub>3</sub>   | 69,5 mm  | Height of the shaft washer   |
| T <sub>5</sub>   | 96 mm    | Distance shaft washer - cage |
| A                | 110 mm   | Distance of the center point |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -30 °C | Operating temperature min. |
| T <sub>max</sub> | 200 °C | Operating temperature max. |



### Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna