



FAG

29444-E1-XL

Axial spherical roller bearing

Axial spherical roller bearing 294..-E1-XL, no flanging ring



X-life

Informacje techniczne



Twoja aktualna wersja produktu

Heat treatment	Standard	Standard
Locating feature, housing washer	Without	
Cage	JP	Sheet metal cage
Handling thread holes	Without	
Constricted width and inclination variation	Standard	
Test certificate	Without	

Main Dimensions & Performance Data

d	220 mm	Bore diameter
D	420 mm	Outside diameter
T	122 mm	Height
C _a	3.500.000 N	Basic dynamic load rating, axial
C _{0a}	10.000.000 N	Basic static load rating, axial
C _{ua}	1.020.000 N	Fatigue load limit, axial
n _G	1.560 1/min	Limiting speed
n _{gr}	790 1/min	Reference speed
≈m	68,3 kg	Masa



Mounting dimensions

$d_{a \min}$	315 mm	Minimum diameter shaft shoulder
$D_{a \max}$	360 mm	Maximum diameter of housing shoulder
$D_{b \min}$	428 mm	Minimum bore diameter housing
$d_{b \max}$	254 mm	Maximum distance sleeve
$d_{b1 \max}$	241 mm	Maximum chamfer diameter of distance sleeve
$r_{a \max}$	5 mm	Maximum recess radius
	30 °	Angle of chamfer of the distance sleeve

Dimensions

D_1	300 mm	Bore diameter housing washer
d_1	379,8 mm	Rip diameter shaft washer
$r_{\min}$	6 mm	Minimum chamfer dimension
T_1	58,5 mm	Height of the housing washer
T_3	77 mm	Height of the shaft washer
T_5	107,5 mm	Distance shaft washer - cage
A	132 mm	Distance of the center point

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna