

**FAG****30/5-B-2RSR-TVH**

Angular contact ball bearing

Angular contact ball bearing 30..-B-2RSR-TVH, double row, seals, plastic cage



Informacje techniczne



Twoja aktualna wersja produktu

Version code	>C	Not marked on bearing
Design variant	B	Bearing without filling slot
Sealing	2RSR	Contact seal on both sides
Cage	TVH	Solid cage made of glass-fiber reinforced polyamide PA66
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	GA14	Ball bearing grease, low noise
Axial internal clearance	CN	Group N (CN)

Main Dimensions & Performance Data

d	5 mm	Bore diameter
D	14 mm	Outside diameter
B	7 mm	Width
C _r	1.780 N	Basic dynamic load rating, radial
C _{0r}	940 N	Basic static load rating, radial
C _{ur}	49 N	Fatigue load limit, radial
n _G	30.500 1/min	Limiting speed
≈m	0,005 kg	Masa



Mounting dimensions

$d_{a\min}$	6,4 mm	Minimum diameter shaft shoulder
$D_{a\max}$	12,6 mm	Maximum diameter of housing shoulder
$r_{a\max}$	0,2 mm	Maximum fillet radius

Dimensions

$r_{\min}$	0,2 mm	Minimum chamfer dimension
D_1	11,21 mm	Shoulder diameter outer ring
D_2	12,7 mm	Caliber diameter outer ring
d_1	8,8 mm	Shoulder diameter inner ring
d_2	8,5 mm	Caliber diameter inner ring
a	6,9 mm	Distance between the apexes of the pressure cones
α	25 °	Contact angle

Temperature range

$T_{\min}$	-20 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie dożywotnie, bezobsługowe
	Smarowanie smarem
	Uszczelnienie dwustronne