


**FAG****30/6-B-2RSR-TVH-L285/15**

Angular contact ball bearing

Angular contact ball bearing 30..-B-2RSR-TVH, double row, seals, plastic cage



Informacje techniczne



Twoja aktualna wersja produktu

Design variant	B	Bearing without filling slot
Sealing	2RSR	Contact seal on both sides
Cage	TVH	Solid cage made of glass-fiber reinforced polyamide PA66
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	L285	Grease (L285/customer specific)
Axial internal clearance	CN	Group N (CN)

Main Dimensions & Performance Data

d	6 mm	Bore diameter
D	17 mm	Outside diameter
B	9 mm	Width
C _r	3.050 N	Basic dynamic load rating, radial
C _{0r}	1.400 N	Basic static load rating, radial
C _{ur}	74 N	Fatigue load limit, radial
n _G	28.000 1/min	Limiting speed
m	0,011 kg	Masa



Mounting dimensions

d _{a min}	8 mm	Minimum diameter shaft shoulder
D _{a max}	15 mm	Maximum diameter of housing shoulder
r _{a max}	0,3 mm	Maximum fillet radius

Dimensions

r _{min}	0,3 mm	Minimum chamfer dimension
D ₁	13,42 mm	Shoulder diameter outer ring
D ₂	14,8 mm	Caliber diameter outer ring
d ₁	9,58 mm	Shoulder diameter inner ring
d ₂	8,3 mm	Caliber diamter inner ring
a	8,8 mm	Distance between the apexes of the pressure cones
α	25 °	Contact angle

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie dożywotnie, bezobsługowe
	Smarowanie smarem
	Uszczelnienie dwustronne