



FAG


30/6-B-TVH

Angular contact ball bearing

Angular contact ball bearing 30..-B-TVH,
double row, plastic cage



Informacje techniczne



Twoja aktualna wersja produktu

Version code	>C	Not marked on bearing
Design variant	B	Bearing without filling slot
Sealing	Without	Not sealed
Cage	TVH	Solid cage made of glass-fiber reinforced polyamide PA66
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Without	Bearing not greased
Axial internal clearance	CN	Group N (CN)

Main Dimensions & Performance Data

d	6 mm	Bore diameter
D	17 mm	Outside diameter
B	9 mm	Width
C _r	3.050 N	Basic dynamic load rating, radial
C _{0r}	1.400 N	Basic static load rating, radial
C _{ur}	74 N	Fatigue load limit, radial
n _G	42.000 1/min	Limiting speed
n _{gr}	32.000 1/min	Reference speed
≈m	10 g	Masa



Mounting dimensions

$d_{a\ min}$	8 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	15 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	0,3 mm	Maximum fillet radius

Dimensions

$r_{\ min}$	0,3 mm	Minimum chamfer dimension
$D_{\ 1}$	13,42 mm	Shoulder diameter outer ring
$D_{\ 2}$	14,8 mm	Caliber diameter outer ring
$d_{\ 1}$	9,58 mm	Shoulder diameter inner ring
$d_{\ 2}$	8,3 mm	Caliber diamter inner ring
a	8,8 mm	Distance between the apexes of the pressure cones
α	25 °	Contact angle

Temperature range

$T_{\ min}$	-30 °C	Operating temperature min.
$T_{\ max}$	120 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia