




**308-NPP-B**

Self-aligning deep groove ball bearings

Informacje techniczne



Twoja aktualna wersja produktu

|                        |     |           |
|------------------------|-----|-----------|
| Sealing                | NPP |           |
| Shape of outer surface | B   | Spherical |

Main Dimensions & Performance Data

|                 |          |                                   |
|-----------------|----------|-----------------------------------|
| d               | 40 mm    | Bore diameter                     |
| D <sub>SP</sub> | 90 mm    | Outside diameter                  |
| B               | 23 mm    | Width                             |
| C <sub>r</sub>  | 47.000 N | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 26.000 N | Basic static load rating, radial  |
| ≈m              | 0,63 kg  | Masa                              |

Dimensions

|                  |         |                                 |
|------------------|---------|---------------------------------|
| d <sub>2</sub>   | 55,6 mm | Rib diameter sealing inner ring |
| r <sub>min</sub> | 0,6 mm  | Minimum chamfer dimension       |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -20 °C | Operating temperature min. |
| T <sub>max</sub> | 100 °C | Operating temperature max. |



### Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne
-  Nieosiowość statyczna