



FAG



X-life

3206-BD-XL-2HRS-L138-C3

Angular contact ball bearing

Angular contact ball bearing 32..-BD-XL-2HRS, double row, X-life, seals, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Design variant	B	Bearing without filling slot
Changed internal design	D	D
Sealing	2HRS	Contact seal on both sides
Cage	JH	Steel sheet metal
Tolerance class	P6	Class 6 (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	L138	Grease (L138/customer specific)
Axial internal clearance	C3	Group 3 (C3), bigger than CN

Main Dimensions & Performance Data

d	30 mm	Bore diameter
D	62 mm	Outside diameter
B	23,8 mm	Width
C _r	31.000 N	Basic dynamic load rating, radial
C _{0r}	22.200 N	Basic static load rating, radial
C _{ur}	1.540 N	Fatigue load limit, radial
n _G	9.000 1/min	Limiting speed
≈m	0,294 kg	Masa



Mounting dimensions

$d_{a\ min}$	35,6 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	56,4 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	1 mm	Maximum fillet radius

Dimensions

$r_{\ min}$	1 mm	Minimum chamfer dimension
$D_{\ 1}$	53,3 mm	Shoulder diameter outer ring
$D_{\ 2}$	55,84 mm	Caliber diameter outer ring
$d_{\ 1}$	42,2 mm	Shoulder diameter inner ring
$d_{\ 2}$	40,33 mm	Caliber diamter inner ring
a	36,4 mm	Distance between the apexes of the pressure cones
α	30 °	Contact angle

Temperature range

$T_{\ min}$	-30 °C	Operating temperature min.
$T_{\ max}$	100 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie dożywotnie, bezobsługowe
	Smarowanie smarem
	Uszczelnienie dwustronne