



FAG



3211-BD-XL-2HRS-TVH

Angular contact ball bearing

Angular contact ball bearing 32...BD-XL-2HRS-TVH, double row, X-life, seals, plastic cage

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design variant	B	Bearing without filling slot
Changed internal design	D	D
Sealing	2HRS	Contact seal on both sides
Cage	TVH	Solid cage made of glass-fiber reinforced polyamide PA66
Tolerance class	P6	Class 6 (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	GA13	Ball bearing and insert bearing grease
Axial internal clearance	CN	Group N (CN)

Main Dimensions & Performance Data

d	55 mm	Bore diameter
D	100 mm	Outside diameter
B	33,3 mm	Width
C _r	61.000 N	Basic dynamic load rating, radial
C _{0r}	51.000 N	Basic static load rating, radial
C _{ur}	3.550 N	Fatigue load limit, radial
n _G	5.300 1/min	Limiting speed
≈m	0,95 kg	Masa



Mounting dimensions

$d_{a\ min}$	64 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	91 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	1,5 mm	Maximum fillet radius

Dimensions

$r_{\ min}$	1,5 mm	Minimum chamfer dimension
$D_{\ 1}$	87,78 mm	Shoulder diameter outer ring
$D_{\ 2}$	90,78 mm	Caliber diameter outer ring
$d_{\ 1}$	71,6 mm	Shoulder diameter inner ring
$d_{\ 2}$	69,18 mm	Caliber diamter inner ring
a	58,5 mm	Distance between the apexes of the pressure cones
α	30 °	Contact angle

Temperature range

$T_{\ min}$	-30 °C	Operating temperature min.
$T_{\ max}$	100 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie dożywotnie, bezobsługowe
	Smarowanie smarem
	Uszczelnienie dwustronne