



FAG



3212-BD-XL-2HRS

Angular contact ball bearing

Angular contact ball bearing 32..-BD-XL-2HRS, double row, X-life, seals, steel sheet metal cage

X-life

Informacje techniczne



Twoja aktualna wersja produktu

|                                  |      |                                         |
|----------------------------------|------|-----------------------------------------|
| Design variant                   | B    | Bearing without filling slot            |
| Changed internal design          | D    | D                                       |
| Sealing                          | 2HRS | Contact seal on both sides              |
| Cage                             | JH   | Steel sheet metal                       |
| Tolerance class                  | P6   | Class 6 (ISO 492:2023)                  |
| Dimensional / heat stabilization | S0   | Rings dimensional stabilized up to 150° |
| Lubricant                        | GA13 | Ball bearing and insert bearing grease  |
| Axial internal clearance         | CN   | Group N (CN)                            |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 60 mm       | Bore diameter                     |
| D               | 110 mm      | Outside diameter                  |
| B               | 36,5 mm     | Width                             |
| C <sub>r</sub>  | 75.000 N    | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 64.000 N    | Basic static load rating, radial  |
| C <sub>ur</sub> | 4.400 N     | Fatigue load limit, radial        |
| n <sub>G</sub>  | 4.750 1/min | Limiting speed                    |
| ≈m              | 1,31 kg     | Masa                              |



Mounting dimensions

|              |        |                                      |
|--------------|--------|--------------------------------------|
| $d_{a\ min}$ | 69 mm  | Minimum diameter shaft shoulder      |
| $D_{a\ max}$ | 101 mm | Maximum diameter of housing shoulder |
| $r_{a\ max}$ | 1,5 mm | Maximum fillet radius                |

Dimensions

|             |           |                                                   |
|-------------|-----------|---------------------------------------------------|
| $r_{\ min}$ | 1,5 mm    | Minimum chamfer dimension                         |
| $D_{\ 1}$   | 97,02 mm  | Shoulder diameter outer ring                      |
| $D_{\ 2}$   | 100,51 mm | Caliber diameter outer ring                       |
| $d_{\ 1}$   | 78,99 mm  | Shoulder diameter inner ring                      |
| $d_{\ 2}$   | 76,58 mm  | Caliber diamter inner ring                        |
| $a$         | 64,7 mm   | Distance between the apexes of the pressure cones |
| $\alpha$    | 30 °      | Contact angle                                     |

Temperature range

|             |        |                            |
|-------------|--------|----------------------------|
| $T_{\ min}$ | -30 °C | Operating temperature min. |
| $T_{\ max}$ | 100 °C | Operating temperature max. |

Właściwości

|                                                                                     |                                     |
|-------------------------------------------------------------------------------------|-------------------------------------|
|  | Obciążenie promieniowe              |
|  | Obciążenie osiowe jednokierunkowe   |
|  | Obciążenie osiowe dwukierunkowe     |
|  | Smarowanie dożywotnie, bezobsługowe |
|  | Smarowanie smarem                   |
|  | Uszczelnienie dwustronne            |