



FAG

32319-A

Tapered roller bearing

Tapered roller bearings 323, main dimensions
acc. to DIN 720, separable

Informacje techniczne



Twoja aktualna wersja produktu

Tolerance class	PN	Normal (ISO 492:2023)
Heat treatment	Standard	
Cage	Standard	Sheet steel cage, window cage, roller-guided
Internal design	Standard	
Quality level	Standard	
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	95 mm	Bore diameter
D	200 mm	Outside diameter
B	67 mm	Width, inner ring
C	55 mm	Width, outer ring
T	71,5 mm	Width, total
C _r	530.000 N	Basic dynamic load rating, radial
C _{0r}	710.000 N	Basic static load rating, radial
C _{ur}	82.000 N	Fatigue load limit, radial
n _G	3.500 1/min	Limiting speed
n _{gr}	2.600 1/min	Thermal speed rating
≈m	9,964 kg	Masa



Mounting dimensions

d _a max	115 mm	Maximum diameter of shaft shoulder
d _b min	109 mm	Minimum diameter of shaft shoulder
D _a min	166 mm	Minimum diameter of housing shoulder
D _a max	186 mm	Maximum diameter of housing shoulder
D _b min	186 mm	Minimum diameter of housing shoulder
C _a min	8 mm	Minimum axial space
C _b min	16,5 mm	Minimum axial space
r _a max	4 mm	Maximum fillet radius of shaft
r _b max	3 mm	Maximum fillet radius of housing

Dimensions

r _{1, 2} min	4 mm	Minimum chamfer dimension of inner ring back face
r _{3, 4} min	3 mm	Minimum chamfer dimension of outer ring back face
a	49 mm	Distance between the apexes of the pressure cones
d ₁	141 mm	Guidance rib diameter of inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Calculation factors

e	0,35	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y	1,74	Dynamic axial load factor
Y ₀	0,96	Static axial load factor

Additional information

T2GD095	Comparative designation to ISO 10317 and ISO 355
---------	--



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia