



FAG

33020

Tapered roller bearing

Tapered roller bearings 330, main dimensions
acc. to DIN 720, separable

Informacje techniczne



Twoja aktualna wersja produktu

Tolerance class	P6X	Class 6X (ISO 492:2023)
Heat treatment	Standard	
Cage	Standard	Sheet steel cage, window cage, roller-guided
Internal design	Standard	
Quality level	Standard	
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	100 mm	Bore diameter
D	150 mm	Outside diameter
B	39 mm	Width, inner ring
C	32,5 mm	Width, outer ring
T	39 mm	Width, total
C _r	225.000 N	Basic dynamic load rating, radial
C _{0r}	395.000 N	Basic static load rating, radial
C _{ur}	48.500 N	Fatigue load limit, radial
n _G	4.450 1/min	Limiting speed
n _{gr}	2.900 1/min	Thermal speed rating
≈m	2,411 kg	Masa



Mounting dimensions

d a max	108 mm	Maximum diameter of shaft shoulder
d b min	109 mm	Minimum diameter of shaft shoulder
D a min	135 mm	Minimum diameter of housing shoulder
D a max	141 mm	Maximum diameter of housing shoulder
D b min	143 mm	Minimum diameter of housing shoulder
C a min	7 mm	Minimum axial space
C b min	6,5 mm	Minimum axial space
r a max	2 mm	Maximum fillet radius of shaft
r b max	1,5 mm	Maximum fillet radius of housing

Dimensions

r 1, 2 min	2 mm	Minimum chamfer dimension of inner ring back face
r 3, 4 min	1,5 mm	Minimum chamfer dimension of outer ring back face
a	29 mm	Distance between the apexes of the pressure cones
d 1	124,7 mm	Guidance rib diameter of inner ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	120 °C	Operating temperature max.

Calculation factors

e	0,29	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y	2,09	Dynamic axial load factor
Y 0	1,15	Static axial load factor

Additional information

T2CE100	Comparative designation to ISO 10317 and ISO 355
---------	--



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia