



FAG



X-life

3314-BD-XL-TVH-C3

Angular contact ball bearing

Angular contact ball bearing 33...BD-XL-TVH, double row, X-life, plastic cage

Informacje techniczne



Twoja aktualna wersja produktu

Design variant	B	Bearing without filling slot
Changed internal design	D	D
Sealing	Without	Not sealed
Cage	TVH	Solid cage made of glass-fiber reinforced polyamide PA66
Tolerance class	P6	Class 6 (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased
Axial internal clearance	C3	Group 3 (C3), bigger than CN

Main Dimensions & Performance Data

d	70 mm	Bore diameter
D	150 mm	Outside diameter
B	63,5 mm	Width
C _r	172.000 N	Basic dynamic load rating, radial
C _{0r}	135.000 N	Basic static load rating, radial
C _{ur}	8.900 N	Fatigue load limit, radial
n _G	4.550 1/min	Limiting speed
n _{gr}	5.100 1/min	Reference speed
m	4,5 kg	Masa



Mounting dimensions

d a min	82 mm	Minimum diameter shaft shoulder
D a max	138 mm	Maximum diameter of housing shoulder
r a max	2,1 mm	Maximum fillet radius

Dimensions

r min	2,1 mm	Minimum chamfer dimension
D 1	129,2 mm	Shoulder diameter outer ring
D 2	133,65 mm	Caliber diameter outer ring
d 1	100,27 mm	Shoulder diameter inner ring
d 2	96,92 mm	Caliber diamter inner ring
a	89,3 mm	Distance between the apexes of the pressure cones
α	30 °	Contact angle

Temperature range

T min	-30 °C	Operating temperature min.
T max	120 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia