




3805-2Z-L404

Angular contact ball bearing

Angular contact ball bearing 38..-B-2RZ-TVH,
double row, shields, plastic cage

Informacje techniczne



Twoja aktualna wersja produktu

Design variant	B	Bearing without filling slot
Sealing	2RZ	Non-contact seal on both sides
Cage	TVH	Solid cage made of glass-fiber reinforced polyamide PA66
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	L404	Grease (L404/customer specific)
Axial internal clearance	CN	Group N (CN)

Main Dimensions & Performance Data

d	25 mm	Bore diameter
D	37 mm	Outside diameter
B	10 mm	Width
C _r	5.900 N	Basic dynamic load rating, radial
C _{0r}	5.500 N	Basic static load rating, radial
C _{ur}	285 N	Fatigue load limit, radial
n _G	15.300 1/min	Limiting speed
n _{gr}	10.300 1/min	Reference speed
≈m	0,036 kg	Masa



Mounting dimensions

d a min	27 mm	Minimum diameter shaft shoulder
D a max	35 mm	Maximum diameter of housing shoulder
r a max	0,3 mm	Maximum fillet radius

Dimensions

r min	0,3 mm	Minimum chamfer dimension
D 1	33,12 mm	Shoulder diameter outer ring
D 2	34,03 mm	Caliber diameter outer ring
d 1	29,1 mm	Shoulder diameter inner ring
d 2	27,92 mm	Caliber diamter inner ring
a	17,9 mm	Distance between the apexes of the pressure cones
α	25 °	Contact angle

Temperature range

T min	-30 °C	Operating temperature min.
T max	120 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie dożywotnie, bezobsługowe
	Smarowanie smarem
	Uszczelnienie dwustronne